

Universal Stone Sealer

Technical Data

Product Description:

A water-based fluoropolymer when applied on natural stone surfaces creates a long-lasting invisible barrier that virtually locks-out oils, grease, water, stains, and dirt. The sealer appears nearly colorless and clear. The pH is 7.5 to 8.5 and it will not damage stone.

Uses:

For protection of all natural stone such as marble, limestone, granite, travertine, and slate, flagstone as well as grout, concrete, brick, Saltillo and clay tile.

Application:

Spread Sealer evenly with a paint roller, brush or lambs wool applicator. Work sealer into stone by spreading with applicator every 15 minutes. Allow contact on stone for 45 to 60 minutes. **On highly polished stone like marble and granite**, wipe off excess, if any, and clean with wet sponge.

Coverage:

Depends on porosity of the stone.

For polished stone:

200 - 300 sq. ft. per quart.

800 - 1200 sq. ft. per gallon

For very porous stone:

50 – 100 sq. ft. per quart

200 – 400 sq. ft. per gallon

Maintenance:

Use Brightstone Clean-N-Seal

Handling and Storage:

Store in closed container. Keep in a cool area and do not allow to freeze.

Caution:

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting; drink large quantities of water.

Eye and skin contact: Flush with water.

Important Notice:

Liability is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier. Brightstone recommends testing any products used on fine stone on a small inconspicuous area to determine its efficacy or unexpected results.

Technical Assistance:

www.brightstn.com

Tel # (800) 899-7193

Or (310) 326-5757

Fax: (310) 326-7971

E-mail: techsupport@brightstn.com